

Page 1 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024

PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lubricant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Tel.: (+49) 0731-1420-0 Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard classHazard categoryHazard statementSkin Irrit.2H315-Causes skin irritation.

Eye Dam. 1 H318-Causes serious eye damage. Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016 Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)



Danger

H315-Causes skin irritation. H318-Causes serious eye damage. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P280-Wear protective gloves / eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Without adequate ventilation, formation of explosive mixtures may be possible. Calcium dihydroxide

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. 3.2 Mixtures

OIZ IIIIXCUI OO	
Calcium dihydroxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	215-137-3
CAS	1305-62-0
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	STOT SE 3, H335

Distillates (petroleum), hydrotreated heavy paraffinic	
Registration number (REACH)	
Index	649-467-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	265-157-1
CAS	64742-54-7
content %	1-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Asp. Tox. 1, H304

Titanium dioxide (in powder form containing 1 % or more of particles	
with aerodynamic diameter <= 10 μm)	



Page 3 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

Registration number (REACH)	01-2119489379-17-XXXX
Index	022-006-002
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Coughing

Dermatitis (skin inflammation)

Irritation of the skin.

Other dangerous properties cannot be ruled out.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic pyrolysis products.

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.



Page 4 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Do not use on hot surfaces.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Observe special regulations for aerosols!

Observe special storage conditions.

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a well ventilated place.



Page 5 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Calcium dihydrox	ide		
WEL-TWA: 1 mg/m3 (9) (WEL-TW	/A, EU)	WEL-STEL: 4 mg/m3 (9) (WE		
Monitoring procedures:		ISO 15202 (Workplace air - Deterr		
		particulate matter by Inductively Co		nission Spectrometry), Part
		1-3 - 2012(Part 1), 2012(Part 2), 2		
		NIOSH 7020 (CALCIUM and comp		
		OSHA ID-121 (Metal and metalloid		
		absorption)) - 2002 - EU project Bo		6 card 42-4 (2004)
	-	OSHA PV2121 (Gravimetric Deter		
BMGV:			Other information:	
Chemical Name	Titanium dioxide ((in powder form containing 1 % or r	nore of particles with	
	aerodynamic dian		·	
WEL-TWA: 10 mg/m3 (total inhala	ble dust), 4 mg/m3	WEL-STEL:		
(respirable dust)				
Monitoring procedures:				
BMGV:			Other information:	
Chemical Name	Butane			
WEL-TWA: 600 ppm (1450 mg/m3	3)	WEL-STEL: 750 ppm (1810 n	ng/m3)	
	3)	Compur - KITA-221 SA (549 459)	ng/m3)	
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures:	3)			
WEL-TWA: 600 ppm (1450 mg/m3	3)	Compur - KITA-221 SA (549 459)	ng/m3) Other information:	
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures:	- -	Compur - KITA-221 SA (549 459)		
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: Chemical Name	3)	Compur - KITA-221 SA (549 459)		
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV:	Propane	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL:		
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: Chemical Name WEL-TWA: 1000 ppm (ACGIH)	Propane	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993		
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: Chemical Name WEL-TWA: 1000 ppm (ACGIH)	Propane	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL: Compur - KITA-125 SA (549 954)		
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: Chemical Name WEL-TWA: 1000 ppm (ACGIH) Monitoring procedures:	Propane	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL: Compur - KITA-125 SA (549 954)	Other information:	
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: Solution Chemical Name WEL-TWA: 1000 ppm (ACGIH) Monitoring procedures: BMGV:	Propane Oil mist, mineral	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL: Compur - KITA-125 SA (549 954)	Other information:	
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: Solution Chemical Name WEL-TWA: 1000 ppm (ACGIH) Monitoring procedures: BMGV: Chemical Name	Propane Oil mist, mineral	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL: Compur - KITA-125 SA (549 954) OSHA PV2077 (Propane) - 1990	Other information:	
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: BMGV: Chemical Name WEL-TWA: 1000 ppm (ACGIH) Monitoring procedures: BMGV: BMGV: Chemical Name WEL-TWA: 5 mg/m3 (Mineral oil, 60)	Propane Oil mist, mineral excluding metal	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL: Compur - KITA-125 SA (549 954) OSHA PV2077 (Propane) - 1990	Other information:	
WEL-TWA: 600 ppm (1450 mg/m3 Monitoring procedures: BMGV: BMGV: 1000 ppm (ACGIH) Monitoring procedures: BMGV: BMGV: Chemical Name WEL-TWA: 5 mg/m3 (Mineral oil, 6 working fluids, ACGIH)	Propane Oil mist, mineral excluding metal	Compur - KITA-221 SA (549 459) OSHA PV2010 (n-Butane) - 1993 WEL-STEL: Compur - KITA-125 SA (549 954) OSHA PV2077 (Propane) - 1990 WEL-STEL:	Other information:	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,49	mg/l	
	Environment - soil		PNEC	1080	mg/kg dw	
	Environment - marine		PNEC	0,32	mg/l	
	Environment - sewage treatment plant		PNEC	3	mg/l	
	Environment - sporadic (intermittent) release		DMEL	0,49	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m3	



Page 6 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Workers / employees	Human - inhalation	Short term, local	DNEL	4	mg/m3	
		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	ma/m3	

Distillates (petroleum), hydrotreated heavy paraffinic							
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note	
	Environment - oral (animal feed)		PNEC	9,33	mg/kg		
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3		
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg		
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3		
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3		

Titanium dioxide (in powe	der form containing 1 % or more	of particles with aerodyna	mic diameter	<= 10 µm)		
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note
	Environmental					
	compartment					
	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water,		PNEC	0,193	mg/l	
	sporadic (intermittent)					
	release					
	Environment - sewage		PNEC	100	mg/l	
	treatment plant					
	Environment - sediment,		PNEC	1000	mg/kg dw	
	freshwater					
	Environment - sediment,		PNEC	100	mg/kg dw	
	marine					
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal		PNEC	1667	mg/kg feed	
	feed)					
Consumer	Human - oral	Long term, systemic	DNEL	700	mg/kg bw/d	
		effects				
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

- United Kingdom | WEL-TWA = Workplace Exposure Limit Long-term exposure limit 8-hour TWA (= time weighted average) reference
 period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU: (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE).
- | WEL-STEL = Workplace Exposure Limit Short-term exposure limit 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
- (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
- Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE).



Page 7 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016 Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

With danger of contact with eyes.

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Aerosol. Active substance: liquid.

According to specification

Characteristic



Page 8 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit: Upper explosion limit:

Flash point:

Auto-ignition temperature: Decomposition temperature:

:Ha

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density: Relative vapour density: Particle characteristics:

9.2 Other information

Explosives:

Oxidising liquids:

There is no information available on this parameter.

There is no information available on this parameter.

Does not apply to aerosols.

There is no information available on this parameter. There is no information available on this parameter.

Does not apply to aerosols. Does not apply to aerosols.

There is no information available on this parameter. There is no information available on this parameter.

Does not apply to aerosols.

There is no information available on this parameter.

Does not apply to mixtures.

There is no information available on this parameter.

Does not apply to aerosols. Does not apply to aerosols. Does not apply to aerosols.

Product is not explosive. Possible build up of explosive/highly

flammable vapour/air mixture.

No

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No decomposition if used as intended.

10.4 Conditions to avoid

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Bremsen-Anti-Quietsch-Paste						
Brake Anti-Squeal Paste (can v	vith brush)					
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.



Page 9 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Symptoms:						n.d.a.
Calcium dihydroxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>2500	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:					OECD 431 (In Vitro Skin Corrosion - Human Skin Model Test)	Non-caustic
Skin corrosion/irritation:				Rabbit	,	Irritant, in vivo
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Dam. 1
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Symptoms:						breathing difficulties, abdominal pain, drowsiness, thirst, fever, sore throat, cornea opacity, coughing, headaches, mucous membrane irritation, fatigue

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral	Analogous
					toxicity - Fixe Dose	conclusion
					Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	Analogous
					Dermal Toxicity)	conclusion
Acute toxicity, by inhalation:	LC50	>5,53	mg/l/4h	Rat	OECD 403 (Acute	Aerosol,
					Inhalation Toxicity)	Analogous
						conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation Test)	Analogous
						conclusion



Page 10 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

0500 450 (1.17)
OECD 473 (In Vitro Negative,
Mammalian Analogous
Chromosome conclusion
Aberration Test) Chinese hamster
ouse OECD 476 (In Vitro Negative,
Mammalian Cell Gene Analogous
Mutation Test) conclusion
ouse OECD 474 (Mammalian Negative,
Erythrocyte Analogous
Micronucleus Test) conclusion
ouse OECD 451 Negative,
(Carcinogenicity Studies) Analogous
conclusion 78
weeks, dermal
at OECD 414 (Prenatal Negative,
Developmental Toxicity Analogous
Study) conclusion
dermal
at OECD 421 Negative,
(Reproduction/Developm Analogous
ental Toxicity Screening conclusion oral
Test)
Asp. Tox. 1
at OECD 408 (Repeated Analogous
Dose 90-Day Oral conclusion
Toxicity Study in
Rodents)
gastrointestinal
disturbances,
diarrhoea
abbit OECD 410 (Repeated Analogous
Dose Dermal Toxicity - conclusion
90-Day)
at Dust, Mist,
Analogous
conclusion 4

Titanium dioxide (in powder fo	rm containing	1 % or more	of particles wit	h aerodynamic d	liameter <= 10 µm)	
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral	
					Toxicity - Up-and-Down	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Mechanical
						irritation possible.
Respiratory or skin				Mouse	OECD 429 (Skin	Not sensitizising
sensitisation:					Sensitisation - Local	
					Lymph Node Assay)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian	Negative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	



Page 11 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose)
Brake Anti-Squeal Paste (can with brush)

Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract).
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		(90d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		(90d)
Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative
· .					Mammalian `	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian	Negative
3 ,					Erythrocyte `	
					Micronucleus Test)	
Aspiration hazard:					,	No
Specific target organ toxicity -	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),					Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Symptoms:					,	ataxia, breathing
•						difficulties,
						drowsiness,
						unconsciousness
						, frostbite,
						disturbed heart
						rhythm,
						headaches,
						cramps,
						intoxication,
						dizziness,
						nausea and
						vomiting.
					1	voilling.

Propane



③B)·

Page 12 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male,
						Analogous
						conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	•
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
· .				typhimurium	Reverse Mutation Test)	Ū
Reproductive toxicity	NOAEC	21,641	mg/l	'	OECD 422 (Combined	
(Developmental toxicity):		1			Repeated Dose Tox.	
(Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Aspiration hazard:					Term constraints and the	No
Symptoms:						breathing
-7						difficulties,
						unconsciousnes
						, frostbite,
						headaches.
						cramps, mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.
Specific target organ toxicity -	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),		, .	J		Repeated Dose Tox.	
inhalat.:					Study with the	
					Reproduction/Developm.	
					Tox. Screening Test)	
Specific target organ toxicity -	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined	
repeated exposure (STOT-RE),		1,0 11	1119/1		Repeated Dose Tox.	
inhalat.:					Study with the	
minaidi.					Reproduction/Developm.	
					Tox. Screening Test)	

11.2. Information on other hazards

Bremsen-Anti-Quietsch-Paste (Pinseldose)										
Brake Anti-Squeal Paste (can w	Brake Anti-Squeal Paste (can with brush)									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Endocrine disrupting properties:						Does not apply				
						to mixtures.				
Other information:						No other				
						relevant				
						information				
						available on				
						adverse effects				
						on health.				

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Bremsen-Anti-Quietsch-Paste (Pinseldose)										
Brake Anti-Squeal Paste (can with brush)										
Toxicity / effect	Toxicity / effect Endpoint Time Value Unit Organism Test method Notes									
12.1. Toxicity to fish: n.d.a.										



B.

Page 13 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

12.1. Toxicity to daphnia:		n.d.a.
12.1. Toxicity to algae:		n.d.a.
12.2. Persistence and		n.d.a.
degradability:		
12.3. Bioaccumulative		n.d.a.
potential:		
12.4. Mobility in soil:		n.d.a.
12.5. Results of PBT		n.d.a.
and vPvB assessment		
12.6. Endocrine		Does not apply
disrupting properties:		to mixtures.
12.7. Other adverse		No information
effects:		available on
		other adverse
		effects on the
		environment.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	160	mg/l	Gambusia affinis	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	457	mg/l		,	marine water
12.1. Toxicity to fish:	LC50	96h	50,6	mg/l			freshwater
12.1. Toxicity to daphnia:	NOEC/NOEL	14d	32	mg/l			marine water
12.1. Toxicity to daphnia:	LC50	96h	158	mg/l			marine water
12.1. Toxicity to daphnia:	EC50	48h	49,1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	184,57	mg/l	Pseudokirchneriell a subcapitata	OEĆD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	48	mg/l		,	freshwater
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Calcium dihydroxide, which is sparingly soluble, presents a low mobility in most soils.
12.5. Results of PBT							Not relevant for
and vPvB assessment							inorganic substances.
12.6. Endocrine							Not to be
disrupting properties:							expected



Page 14 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

12.7. Other adverse effects:					pH-value of > 12 will rapidly
Circois.					decrease as
					result of dilution
					and
					carbonation.,
					Even though this
					product can be
					used to
					neutralise over-
					acidified water,
					when 1g/l is
					exceeded
					organisms in the
					water may be
					affected
					adversely.
Toxicity to bacteria:					In high
Toxiony to bastona.					concentrations
					the product
					provokes an
					increase in
					temperature and
					of the pH-value.
					It is used to
					sanitise sewage
					sludge
Other organisms:	NOEC/NOEL		2000	mg/kg dw	soil
				3 3 1	macroorganisms
Other organisms:	NOEC/NOEL		12000	mg/kg dw	soil
					microorganisms
Other organisms:	NOEC/NOEL	21d	1080	mg/kg	terrestrial plants

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to fish:	NOEC/NOEL	28d	>1000	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	10	mg/l	Daphnia magna	QSAR	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	48h	>100	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=100	mg/l	Pseudokirchneriell a subcapitata	OEĆD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	31	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable, Analogous conclusion
12.2. Persistence and degradability:		28d	6	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable



Page 15 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

12.3. Bioaccumulative potential:	Log Pow	3,9-6			High
12.5. Results of PBT and vPvB assessment					No PBT substance, No vPvB substance
Other information:	AOX	0	%		

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
40.4 Tardaltuta alman	F050	701-	10		De a coda bina bina ni a II	Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriell	U.S. EPA-600/9-	
12.2. Persistence and					a subcapitata	78-018	Not relevant for
degradability:							
degradability.							inorganic substances.
12.3. Bioaccumulative	BCF	42d	9,6				Not to be
potential:	501	720	3,0				expected
12.3. Bioaccumulative	BCF	14d	19-352				Oncorhynchus
potential:							mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas		
					fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance



Page 16 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

12 01 12 spent waxes and fats

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

15 01 04 metallic packaging

15 01 10 packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:
- 14.5. Environmental hazards:
- Not ap

14.5. Environmental hazards:

Tunnel restriction code:

Not applicable
D

Classification code: 5F LQ: 1L Transport category: 2

Transport category:

Transport by sea (IMDG-code)

14.1. UN number or ID number:

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards:Not applicableMarine Pollutant:Not applicableEmS:F-D, S-U

Transport by air (IATA)

14.1. UN number or ID number: 1950

14.2. UN proper shipping name: UN 1950 Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.













Page 17 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

_ acceraing to eterage, marraining eter	<i>-</i>		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

DITCOUVE ZOTZ/TO/LO (OCT	7030 III <i>)</i> , AIIIICX I, I alt Z	s product contains the substan	noco notou bolow.	
Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity
			(tonnes) for the	(tonnes) for the
			application of - Lower-tier	application of - Upper-tier
			requirements	requirements
18	Liquefied flammable	19	50	200
	gases, Category 1 or 2			
	(including LPG) and			
	natural gas			

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

< 3,85 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

2

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

ssification according to calculation procedure.
ssification according to calculation procedure.



Page 18 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H351 Suspected of causing cancer by inhalation.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Skin Irrit. — Skin irritation Eye Dam. — Serious eye damage

Aerosol — Aerosols

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Asp. Tox. — Aspiration hazard

Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

according, according to acc., acc. to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Article number Art., Art. no.

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

European Inventory of Existing Commercial Chemical Substances **EINECS**

ELINCS European List of Notified Chemical Substances



Page 19 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016

Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose) Brake Anti-Squeal Paste (can with brush)

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

mg/kg bw mg/kg body weight

mg/kg bw/d, mg/kg bw/day mg/kg body weight/day

mg/kg dw mg/kg dry weight mg/kg wwt mg/kg wet weight n.a. not applicable

n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:



③B)·

Page 20 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.03.2024 / 0016 Replacing version dated / version: 17.01.2024 / 0015

Valid from: 04.03.2024 PDF print date: 08.03.2024

Bremsen-Anti-Quietsch-Paste (Pinseldose)
Brake Anti-Squeal Paste (can with brush)

Brake Anti-Squeal Paste (can with brush) Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90 © by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.