

TECHNICAL CHARACTERISTICS

SYNTIUM 5000 RN

PRODUCT CODE: 1832

APPLICATION

Syntium 5000 RN has been specifically designed to help prolong the life and maintain the efficiency of emission systems in diesel passenger car vehicles.

Syntium 5000 RN is particularly suitable for diesel engines equipped with particulate filters for manufacturers such as Renault.

Syntium 5000 RN is also suitable for some gasoline applications.

SPECIFICATIONS

SAE 5W-30, ACEA C4, MB-Approval 229.51, MB-Approval 226.51, RENAULT RN0720

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
ASPECT			С & В
DENSITY 15°C	ASTM D 4052	g/cm³	0,852
VISCOSITA' @ 100°C	ASTM D 445	cSt	12
VISCOSITY INDEX	ASTM D 2270		167
VISCOSITY @ -30°C	ASTM D 5293	cPs	6300
FLASH POINT CI. O. C.	ASTM D 92	°C	>200
POUR POINT	ASTM D 97	°C	<-40
FOAM @ 24°C	ASTM D 892	cc/s	0 / 0
T.B.N.	ASTM D 2896	mg KOH/g	8.2

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

05/2015