Product information Anti-bacterial Diesel additive

Description

Highly effective biocide with broad spectrum of activity against bacteria, yeast and mold. Use biocides safely. Always read the label and product information before use.

Properties

- active in preventing bacterial infestation
- decontaminates infested tank systems
- keeps injection nozzles clean
- reduces pollutant emissions
- improves the lubrication properties
- prevents expensive repairs

Technical data

Base	biocide, detergent and cetan number enhancer
Color / appearance	brown, clear
Density at 15 °C	0,905 g/cm³
Viscosity at 40 °C	<7 mm²/s
Flash point	63 °C
Regulation on Flammable Liquids Class (Germany)	A III
Shelf life in original sealed container	5 years
Odor	charakteristisch, characteristic
Form	liquid

Areas of application

For preventive use in diesel-powered vehicles which are decommissioned for long periods or are infrequently used such as construction machinery, commercial vehicles, RVs, passenger cars or in storage tanks or for disinfection of contaminated tank systems. Not suitable for use with HVO diesel fuel.

Application

Dosage 1:1000. 25 ml sufficient for 25 l of diesel fuel. For preventative use, add the corresponding amount before filling the tank. With serious bacterial and fungal infestation with filter clogging, use a booster dose (dosage 1:200).

Available pack sizes

125 ml Can sheet metal	207.10
	I-GR
1 l Can sheet metal	2368
	GB-DK-FIN-N-S
1 l Can sheet metal	21317
	D-GB-F-I-NL-GR

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Available pack sizes

1 l Can sheet metal	21642 D-E-P
5 l Canister plastic	21318 D-GB-E
60 l Black plate barrel	21319 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.



