

## Leichtlauf Performance 5W-30



### Description

Low-friction motor oil for gasoline and diesel vehicles with and without diesel particulate filter (DPF) and turbocharger. Protects against wear, reduces oil and fuel consumption and ensures fast oil penetration of the engine.

### Properties

- high wear resistance
- high lubrication reliability
- long engine service life
- especially suitable for vehicles with diesel particulate filter
- reduces pollutant emissions
- tested for turbochargers and catalytic converters
- smooth engine running
- instant lubrication after cold start
- reduces fuel consumption
- optimum oil pressure under all operating conditions
- high shear stability
- optimum stability to aging
- outstanding engine cleanliness
- miscible with all commercially available motor oils

### Specifications / Approvals

ACEA C3 • API SP

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required**

ACEA C2 • MB 229.31

### Technical data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,850 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	71,7 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	12,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	<= 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	165 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-36 °C DIN ISO 3016

### Technical data

Evaporation loss (Noack)	11,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	8,0 mg KOH/g DIN ISO 3771
Sulfate ash	<= 0,8 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

### Areas of application

For gasoline and diesel engines with multi-valve technology, Valvetronic and turbocharging (with or without charge air cooling). Also ideal for use in gas-driven vehicles (CNG/LPG).

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Canister plastic	21388 ALGERIEN-GB-ARAB-F
1 l Canister plastic	21363 BOOKLET
4 l Canister plastic	21592 BOOKLET
5 l Canister plastic	21389 ALGERIEN-GB-ARAB-F
5 l Canister plastic	21364 BOOKLET
20 l Canister plastic	21365 D-GB-I-F-E-P-DK-FIN-N-S
60 l Black plate barrel	21451 D-GB
205 l Black plate barrel	21366 D-GB

## Product information

PI 17/04/21/2023



## Leichtlauf Performance 5W-30

**Our information is based on thorough research and may be considered reliable, although not legally binding.**